# e. **HOFMANN** PLASTICS

### TECHNICAL DATA

Capacity under lid	0.95lt / 32oz	
Wall Thickness	Container HT32-B (Pineapple): 0.37mm 0.015in Lid HTL115: 0.30mm 0.012in	
Weight (approx.) without bail	Container HT32-B (Pineapple): 17.1g 0.603oz Lid HTL115: 4.2g 0.150oz	
Material	Polypropylene	
Printing	Dry Offset - Up to 6 Colours	
Colour	Clear	

#### **OPENING & CLOSING**

TO OPEN: Peel and lift cover.

TO CLOSE: Place lid on container. Snap on then follow rim around while releasing air by pressing on center of lid to burp container. If using a closing device use proper burping function.

#### RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

#### APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

#### PRODUCT CODE

## **CONTAINER:** #HT32-B (Pineapple) **LID:** #HTL115 #HTL409



#### DIMENSIONS

Container Height	13.50	5.31
Container Height with Lid	13.61	5.36
Upper width with Lid	12.10	4.76
Lower Width	9.07	3.57

СМ

INCHES

#### PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty containers: 500 per box - 10,000 per skid
- Warehousing of Lids: #HTL115: 500 per box - 32,000 per ski
- 500 per box 24,000 per skid
- Max 1 pallet high for warehousing of empty containers and lids



E. Hofmann Plastics Inc. • 51 Centennial Road, Orangeville, Ontario, Canada L9W 3R1 Telephone: 519-943-5050 • Toll Free: 1-877-707-Pail • Fax: 519-938-5349 • www.hofmannplastics.com